

## Technical Data

Type	2 hook
Operation	Lever/lever
Pz (mm)	92
Backset (mm)	35, 45
Faceplate (mm)	16

### Material Specification

Lock Case	Steel acc. En 10149/zinc plated
Face Plate	Steel acc. En 10149
Latch Bolt	Zinc diecasting acc. 1743-2/nickel plated En 12540
Deadbolt	Zinc diecasting acc. 1743-2/nickel plated En 12540
Spindle Square	Brass acc. DIN 1709
Handle-Spring Housing	Zinc diecasting acc.. 1743-2/yellow bichromated En 12330
Handle-Spring	Steel acc. DIN 2076-D
Drive Gear	Steel acc. En 10149
Slider	Steel acc. En 10149/zinc plated
Tumbler	Zinc diecasting acc. 1743-2/nickel plated En 12540
Tumbler Spring	Steel acc. DIN 2076-D
Box Quantity	5



## AS 4900 2 Hook

Multipoint door lock for use on residential door applications.

The lock is a lever operated multipoint lock featuring 2 hardened steel hooks, a reversible latch and an anti-saw deadbolt as standard.

- Twin hardened steel hooks for security
- Suits standard 92mm Pz handles

### Part Numbers

Description	Type	Backset (mm)	Hooks	Part No.
AS4900 Multipoint Lock	Standard	35	2	047786
AS4900 Multipoint Lock	Standard	45	2	047790*

\* special order only

### Guarantees & Accreditations

Mechanical Guarantee	5 years
Labour Guarantee	2 years



to place your order simply call our sales team direct on 01327 312 400